

CV RUNDAWA TEKNIK

Jl. Cihanjuang No. 182, Kota Cimahi,Jawa barat , Indonesia , 40513

Mobile phone : 0812 2196 117

www.generalkontraktor.co.id

NO.	TYPE	U R A I A N	Q'TY	HARGA SATUAN (Rp.)
120	RE-100	AIR PERMEABILITY OF PORLAND CEMENT BY FINENESS DEVICE ASTM C-204 / AASHTO T-153 <u>Consist of :</u>	1 set	3,000,000
	RE-101	Stand Polished wood	1 pc	
	RE-102	U-Tube Manometer Glass tubing with valve.	1 pc	
	RE-103	Permeability Cell Stainless steel.	1 pc	
	RE-104	Perforated Disc Non corroding metal.	1 pc	
	RE-105	Plunger Stainless steel.	1 pc	
	RE-107	Stock Solution Dibutylphtalate.	0.3 ltr	
	RE-108	Filter Paper Type 1, grade B.	1 box	
	RG-473	Funnel Glass.	1 pc	
121	RE-110	SPECIFIC GRAVITY OF HYDRAULIC CEMENT TEST ASTM C-188 / AASHTO T-133 <u>Consist of :</u>	1 set	1,000,000
	RE-111	Le Chatelier Flask 250 ml cap., the neck graduated 0-1 ml and 15-24 ml.	1 pc	
	RE-112	Kerosene Deaired kerosene.	1 ltr	
	RG-473	Funnel Glass, narrow mouth.	1 pc	
	RG-521	Wash Bottle Plastic, 250 ml capacity.	1 pc	
	RG-530	Pipette Glass, 5 ml capacity.	1 pc	
	RG-600	Thermometer Glass, 0 - 50 deg.C	1 pc	
	RG-820	Spatula 150 mm blade length.	1 pc	
	RG-922	Soft Brush Round type.	1 pc	
122	RE-120	TIME OF SETTING OF HYDRAULIC CEMENT BY VICAT NEEDLE ASTM C-187/C-191; T-129/T-131 <u>Consist of :</u>	1 set	2,500,000
	RE-121	Vicat Apparatus Cast alumunium frame stainless steel rod. 0 - 50 mm scale.	1 pc	
	RE-123	Initial needle Steel needle, 1 mm dia, with footing, brass thread.	1 pc	
	RE-124	Final needle Steel needle, 1 mm dia, brass thread.	1 pc	
	RE-125	Conical Ring Mold 70 mm base dia, 60 mm top dia, 40 mm height.	1 pc	
	RE-126	Glass plate 10 mm thick, 12 x 12 cm.	1 pc	

NO.	TYPE	U R A I A N	Q'TY	HARGA SATUAN (Rp.)
123	RE-160	COMPRESSIVE STRENGTH OF HYDRAULIC CEMENT MORTAR ASTM C-109 / AASHTO T-106 <u>Consist of :</u> Cement Cube Mold Cast iron, 3 gang , 2" x 2" x 2" Flow Table, Hand operated. <u>Consist of :</u> Frame Welded steel, 10" dia., 1/2" drop, brass table. Flow Mold Brass, base 101.6 mm dia top 69.85 mm dia., height 50.8 mm. Vernier Caliper 300 mm capacity. Tamper Plastic, 1/2" x 1" face. Glass Plate 10 mm thick, 30 x 30 cm. Graduated Cylinder 250 ml capacity. Scraper Plastic handle.	1 set 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc	5,500,000 
124	RE-160 A	COMPRESSIVE STRENGTH OF HYDRAULIC CEMENT MORTAR ASTM C-109 / AASHTO T-106 <u>Consist of :</u> Cement Cube Mold Cast iron, 3 gang , 2" x 2" x 2" Flow Table Electric, 100 rpm, 220 volt, 1 ph, 100 watt. <u>Consist of :</u> Frame Welded frame, brass table 10" dia., 1/2" drop. Flow Mold Brass, base 101.6 mm dia top 69.85 mm dia, height 50.8 mm. Tamper Plastic, 1/2" x 1" face. Vernier Caliper 300 mm capacity. Glass Plate 10 mm thick, 30 x 30 cm. Graduated cylinder 250 ml capacity. Scraper Plastic handle.	1 set 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc 1 pc	7,250,000 
125	RE-170	COMPRESSION MACHINE ASTM C-109	1 set	29,000,000
126	RE-175	COMPRESSION MACHINE ASTM C-109 Mesin Uji TEKAN Hydraulic hand pump, kapasitas 250 kN, 12" diameter Force Gauge (terkalibrasi JNK), berfungsi untuk mengetahui kekuatan tekan kubus mortar semen dengan ukuran 2" x 2" x 2" atau sample silinder berdiameter 2" x 4" tinggi. Dimensi alat 50 x	1 set	35,000,000 